

Specifications

Windows Custom-Application Terminal

- Based on Windows XP Embedded operating system
- Integrated Microsoft RDP and Citrix ICA protocols and terminal emulation
- Integrated LCD flat-panel design
- 256MB FLASH
- 256MB DRAM

Display Support

- VESA monitor support
- Video: selectable, up to 1024 x 768 @ 32-bit color
- Flicker-free, 75 Hz maximum refresh rate

Audio

- Output: 1/8-inch mini, full 16-bit stereo, 48 KHz sample rate
- Integrated speakers
- Input: 1/8-inch 8-bit mini microphone

Input/Output

- Keyboard: enhanced PS/2 with Windows keys (104 keys)
- Mouse: PS/2 wheel mouse included
- Local and/or network printers supported
- Two USB ports
- Serial port, up to 115.2KB, DB-9
- Bi-directional Centronics-compatible parallel port, DB-25

Networking

- TCP/IP with DNS and DHCP
- 10/100 Base T Ethernet with WakeOnLAN, twisted pair (RJ-45)

Server OS Compatibility/Support

- Microsoft Windows 2000/2003
- Microsoft Windows NT Server 4.0, Terminal Server Edition
- Citrix WinFrame® and MetaFrame®

Expandability

- PCI slot
- Hardware options include:
 - 512MB RAM upgrade
 - Internal USB 802.11b
 - Internal CD-ROM or DVD
- See www.wyse.co.uk for availability information

Communication Protocols/Terminal Emulations Supported

- Microsoft Internet Explorer 6.0 resident: HTML, JavaScript, XML, Active X, JVM, Media Player 6.4, Shockwave, Flash, Citrix Nfuse
- RDP 5
- ICA 6, Program Neighborhood
- Pericom TeemNT 1.6 terminal emulation suite

Management

- Send messages
- Complete image upgrade
- Wake terminal remotely (10/100 Base T Ethernet with WakeOnLAN)
- Terminal configuration (IP information, name, etc.)
- Reporting
- Remote management, configuration, and upgrades through Rapport for Wyse client management software (included)

Set-Up and Configuration

- User interface
- Local boot
- 42 standard keyboard languages supported

Configuration

- PXE (image updating standard)
- Remote screen shadowing

Physical Characteristics (H x W x D)

- 14.6in x 14.2in x 7in
- 37cm x 36cm x 17.8cm

Environmental

Operating temperature range

- Operating: 50° to 104°F (10° to 40° C)
- Storage: -4° to 140°F (-20° to 60° C)
- Fanless design

Humidity

- 20% to 80% noncondensing

Operating altitude range

- 0 to 10,000 feet (0 to 3,050 meters)

Power

- Worldwide auto-sensing 100-240 VAC, 47-63 Hz

Regulatory compliance

- | | |
|------------------------|---------------|
| RF interference | Safety |
| ▪ FCC Class B | ▪ UL 60950 |
| ▪ CE mark | ▪ CSA 60950 |
| ▪ TÜV GS | ▪ C-Tick |
| ▪ VCCI (9/03) | |

Power

n EPA Energy Star

Ergonomics

- EK1-ITB-2000
- ISO 13406-2

Warranty

- One-year limited hardware warranty



Wyse Technology (UK) Ltd
 1 The Pavilions, Ruscombe Park,
 Twyford, Berks RG10 9NN
 England
 +44 (0)118 934 2200

Wyse Technology GmbH
 Humboldtstr. 10
 D-85609 Aschheim-Dornach
 Deutschland
 +49-(0)89-46 00 99-0

Wyse Technology
 Immeuble Mercure, 6 Parc Club Ariane
 F-78284 Guyancourt Cedex
 France
 +33 (0)1 39 44 00 44

Websites

EMEA
www.wyse.fr
www.wyse.co.uk
www.wyse.de

OCEANIA
www.wyse.com.au

US
www.wyse.com



©2003 Wyse, WY, and WyseWorks are registered trademarks, and Winterm and Wyse Expedian are trademarks of Wyse Technology Inc. Rapport is a trademark of Rapport Technologies Inc, a division of Wyse Technology Inc. Citrix, ICA, MetaFrame, and WinFrame are registered trademarks of Citrix Systems, Inc. Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. Specifications subject to change without notice. Some features require support by server operating system and protocol. A printed copy of the Wyse End User License Agreement (License) is included in the product's shipping box and is provided for your reference only. The License at www.wyse.com/products/winterm/quickstart/9000.htm as of the purchase date is the controlling licensing agreement. By copying, using, or installing the software or the product you agree to be bound by those terms.